EMC® ScaleIO®

Version 2.0.x

Stateless ESXi Mode Technical Notes

P/N 302-003-504

REV 03

EMC²

Copyright © 2016-2017 Dell Inc. or its subsidiaries. All rights reserved.

Published March 2017

Dell believes the information in this publication is accurate as of its publication date. The information is subject to change without notice.

THE INFORMATION IN THIS PUBLICATION IS PROVIDED "AS-IS." DELL MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WITH RESPECT TO THE INFORMATION IN THIS PUBLICATION, AND SPECIFICALLY DISCLAIMS IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. USE, COPYING, AND DISTRIBUTION OF ANY DELL SOFTWARE DESCRIBED IN THIS PUBLICATION REQUIRES AN APPLICABLE SOFTWARE LICENSE.

Dell, EMC, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be the property of their respective owners. Published in the USA.

EMC Corporation
Hopkinton, Massachusetts 01748-9103
1-508-435-1000 In North America 1-866-464-7381
www.EMC.com

CONTENTS

Chapter 1 Running ScaleIO in ESXi Stateless Mode 5
Stateless ESXi overview....6
Configuring with stateless ESXis overview....6
Preparing the base ESXi image....6
Preparing the host profile....9
Editing the host profile....9
Attaching the ESXi hosts to the host profile....11
Verifying that the ESXis are connected....11

CHAPTER 1

Running ScaleIO in ESXi Stateless Mode

This document describes how to run ScaleIO in ESXi Stateless mode. Topics include:

- Stateless ESXi overview 6
- Configuring with stateless ESXis overview 6

Stateless ESXi overview

The stateless ESXi feature in vCenter allows managing and monitoring ESXi installations. When a host is configured as stateless, it does not preserve its state across reboots, and prevents live installations of VIBs. Each time the ESXi boots, it is reinstalled from a predefined image. Stateless ESXi simplifies updates to the hypervisor and VIB since they can be managed from one central point, without the need to update and install each host manually.

VMWare provides the PowerCLI tool, which is used to build ESXi image profiles and to apply them to a host using deploy rules. After the image profile is created and the deploy rules are configured, the hosts will boot up and the configured image profile will be installed on each host.

In order to preserve essential settings on the ESXi when it is reinstalled, such as network configuration and kernel module parameters, vCenter manages entities called host profiles. Host profile contains settings that can be applied to multiple hosts. Multiple hosts can be attached to a single host profile, with some customization allowed for each individual host. Some settings, such as the kernel module parameters, are configured per host profile and are applied to all hosts attached to this profile. Other settings, such as IP addresses and IQN identifiers, are configured individually for each host.

Configuring with stateless ESXis overview

Using stateless mode for the ESXis that host the SDCs allows for automated host configuration, and ensures that the hosts are configured consistently.

The following steps are necessary to configure the ScaleIO system with stateless ESXis:

1. Use PowerCLI to configure the base ESXi host with the settings you wish to replicate for the remaining ESXis.

   Note

   Stateless systems cannot run hyper-converged, sharing local storage.

2. Create a profile based on the base ESXi.
3. Edit the profile to configure the MDM IP addresses and other SDC settings.
4. Attach the ESXis to the profile.
5. Verify that the SDCs installed on these ESXis are connected to the system.

Preparing the base ESXi image

Prepare an ESXi with the base configuration.

Before you begin

Ensure you have the following:

- vCenter with several ESXis
- Offline bundle file with the appropriate ESXi image
- Offline bundle of the SDC
- Offline bundle of the host profile: `sio-sdc-host-profile-X.XX.xxx.zip`

Use VMware's PowerCLI to run the following commands:

Procedure

1. Connect to the vCenter: `Connect-VIServer -Server <VC_IP> -Protocol https -User <VC_username> -Password <VC_password>`

   where:

   - *<VC_IP>* is the IP address of the vCenter server.
   - *<VC_username>* is the username to log in to the vCenter.
   - *<VC_password>* is the password.

2. Clean previous deployment rules:

   a. Retrieve the list of deployment rules: `Get-DeployRule`

   b. Delete the list of deployment rules: `Remove-DeployRule --delete`

3. Run `Add-EsxSoftwareDepot` to add the following files to the ESXi depot:

   - Offline bundle with ESXi image
   - Offline bundle of the SDC
   - Offline bundle of the host profile

4. Create a new image profile:

   a. Create a new image profile: `New-EsxImageProfile -CloneProfile <IMAGE_PROFILE> -Name "<PROFILE_NAME>" -Vendor DELLEMC`

   where:

   - *<IMAGE_PROFILE>* is the name of the image profile you want to clone.
   - *<PROFILE_NAME>* is the name you wish to call the ESXi image profile.

   For example:

   ```
   New-EsxImageProfile -CloneProfile ESXi-5.5.0-2015xxxxx-
   standard -Name "image_profile_2.0.1" -Vendor DELLEMC
   ```

   b. Display image profile details: `Get-EsxImageProfile`

5. Set the acceptance level of the image profile: `Set-EsxImageProfile -AcceptanceLevel CommunitySupported -ImageProfile <PROFILE_NAME>`

   where *<PROFILE_NAME>* is the name of the image profile.

   ```
   Set-EsxImageProfile -AcceptanceLevel CommunitySupported -
   ImageProfile "image_profile_2.0.1"
   ```

6. Add the offline bundles to the current session: `Add-EsxSoftwarePackage -ImageProfile <PROFILE_NAME> -SoftwarePackage <SDC_OFFLINE_BUNDLE>,<HOST_PROFILE> -Force`

   where:

   - *<PROFILE_NAME>* is the name of the ESXi image profile created above.
   - *<SDC_OFFLINE_BUNDLE>* is the filename of the SDC offline bundle.
   - *<HOST_PROFILE>* is the filename of the host profile.

For example:

```
Add-EsxSoftwarePackage -ImageProfile image_profile_2.0.1 -
SoftwarePackage scaleio-sdc-esx5.5,hostProfiles-
sdcHostProfile-28 -Force
```

7. Create a rule that assigns the image profile to hosts that have a particular IPv4 address pattern:

   a. Create the new rule: `New-DeployRule -name "<RULE_NAME>" -Item <PROFILE_NAME> -pattern "mac=xx:yy:zz:aa:bb:cc"`

      where

      - *<RULE_NAME>* is a name for the new rule.
      - *<PROFILE_NAME>* is the name of the ESXi image profile created above.

      For example:

      ```
      New-DeployRule -name "rule_image_profile_2.0.1" -Item
      image_profile_2.0.1 -pattern "mac=90:e2:ba:74:36:6c"
      ```

   b. Add the rule to the working rule set and activate it: `Add-DeployRule <RULE_NAME>`

      where *<RULE_NAME>* is the name of the new rule created above.

      For example:

      ```
      Add-DeployRule rule_image_profile_2.0.1
      ```

   c. Retrieve the current working rule set: `Get-DeployRuleSet`

8. Check whether each ESXi host is compliant with the new rule by running the following on each ESXi: `Test-DeployRuleSetCompliance x.x.x.x`

   If you encounter any issues with the rule compliance, perform the following for each host to clear any previous configurations:

   a. Repair the AutoDeploy cache to clear previous rules that may have been attached to the ESX: `Repair-DeployImageCache`

   b. Create a variable for the host: `$<VAR_NAME>=Get-VMHost -Name <HOST_IP_ADDRESS>`

      ```
      $host173=Get-VMHost -Name 192.168.110.161
      ```

   c. Associate the specified image profile with the specified system: `Apply-ESXImageProfile -ImageProfile <NEW_PROFILE> -Entities <ESX_HOST>`

   d. Test and repair the rule set compliance: `$host | Test-DeployRuleSetCompliance | Repair-DeployRuleSetCompliance`

   e. Retest the rule set compliance: `Test-DeployRuleSetCompliance <HOST_IP_ADDRESS>`

9. Reboot all the ESXi hosts.

Results

The ESXi image profile is created with the necessary rules.

Preparing the host profile

Prepare the host profile settings based on the previously configured ESXi.

Procedure

1. Open the vSphere Web Client.
2. Navigate to the Host profiles view.
3. Click the **Extract Profile from a Host** icon (+).



4. Select the previously configured ESXi from which to extract the profile settings and click **Next**.
5. Type the name and enter a description for the new profile and click **Next**.
6. Review the summary information for the new profile and click **Finish**.

Editing the host profile

In vSphere, edit the host profile's settings.

Before you begin

Ensure you have the IP addresses for the MDMs, or the virtual IP address for the MDM cluster.

Edit the host profile's settings to include the IP addresses for the MDMs. This allows the stateless ESXi to serve as an SDC. You can optionally configure other SDC options.

Procedure

1. In the vSphere Web Client, navigate to the Host Profiles view and select the host profile name.
2. Click **Actions** > **Edit Settings...**.



3. In the **Name and Description** screen, select the host profile you wish to edit and click **Next**.
4. In the **Edit Host Profile** screen, expand the **General System Settings** folder.
5. Expand **Kernel Module Configuration**.
6. In the list of modules, scan to see if the **scini** module appears. If it does, clear the checkbox.
7. Expand the **Other** folder.
8. In the list of profile settings, identify the setting that updates the MDM IP addresses.

   In the right pane, the setting name is displayed as **IoctlMdmIPStr**.



9. In the **Value** field below the setting name, enter the MDM IP addresses, and click **Next**.

   Use commas to separate the IP address of each MDM, or use a virtual IP address for the MDM cluster.
10. Review the summary information for the edited profile and click **Finish**.

Attaching the ESXi hosts to the host profile

Attach the ESXis to the host profile.

Procedure

1. In the vSphere Web Client, navigate to the Host Profiles view.
2. Select the created host profile.
3. Select **Actions** > **Attach/Detach Hosts and Clusters**.
4. In the **Select Hosts/Clusters** screen, select the ESXis you wish to attach to the host profile and click **Finish**.



5. Reboot all ESXis that were attached to the profile.

Verifying that the ESXis are connected

Use the GUI to verify that the ESXis are connected to the system.

Before you begin

Ensure that you have:

- The management IP address or hostname of the MDM.
- The username and password to log in to the GUI.

Procedure

1. Open the GUI.
2. Log in using the MDM IP address or hostname and the username and password.
3. In the **Frontend** > **SDCs** view, verify that all of the ESXis hosting SDCs are connected.